Engine Model	E225LHO E225LH E225XH E225XCH
Colour	5 colours available over 400 colour combinations
Engine Type	V6 74° E-TEC
Bore x Stroke - mm	98 x 76
Displacement - cc	3441
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg	244 248 253
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	133 Amps Total / 50 net Dedicated
Steering	Remote
Hydraulic Steering	Integrated
Dynamic Power Steering	Integrated Accessory
Trim Method	Power Trim & Tilt + i-Trim
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - in	20 25
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L	On-Engine 7.5
Recommended Oil	Evinrude XD-100
Recommended Fuel	87 Octane
Counter Rotation	Available 25 inch
Warranty	5-Year Engine** / 5-Year Corrosion
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union
Integrated Features	Clean Dual Axis Rigging, i-Trim, auto-winterization, no break-in period
Accessories	Evinrude E-Link, ICON 7.0 touch screen, cover, steering support brace, foot throttle, flush kit



Price is valid with plack or write panels, in unite bounds an up-distingers applied.
Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V.
Net dedicated battery charging power output is 50 Amp.
*BRP 5 YEAR (STANDARD 3 + 2) This Extended Limited Warranty Program adds 24 months of BRP Limited Warranty coverage beyond the standard 36 month BRP Warranty applicable to Evinrude outboard engines under special conditions (see the Evinrude 2017 catalog for more details). Offered only through BRP European Distribution SA and its authorized BRP dealers for Evinrude" outboard engines that are sold to residents of the European Union for recreational use only.



 $^{^{(1)}}$ Price is valid with black or white panels, for other colors an up-charge is applied