

EVINRUDE® E-TEC® G2™ ENGINE SPECIFICATIONS

E 300

| | | |
|--------------------------------|-------------------------------------------------------------------------------------------------|--------------------------|
| Engine Model | E300LU | <input type="checkbox"/> |
| | E300XU | <input type="checkbox"/> |
| | E300XCU | <input type="checkbox"/> |
| | E300ZU | <input type="checkbox"/> |
| | E300ZCU | <input type="checkbox"/> |
| | A300XCU | <input type="checkbox"/> |
| A300ZCU | <input type="checkbox"/> | |
| Colour | 5 colours available over 400 colour combinations | |
| Engine Type | V6 74° E-TEC | |
| Bore x Stroke - mm | 98 x 76 | |
| Displacement - cc | 3441 | |
| Gear Ratio | 1.85:1 | |
| Full Throttle RPM Range | 5400-6000 RPM | |
| Weight - kg | 253 | <input type="checkbox"/> |
| | 258 | <input type="checkbox"/> |
| | 283 | <input type="checkbox"/> |
| Starting | Electric | |
| Controls | Integrated Digital Shift & Throttle | |
| Fuel Induction | E-TEC Direct Injection with stratified low RPM combustion mode | |
| Alternator Output* | 133 Amps Total / 50 net Dedicated | |
| Steering | Remote | |
| Hydraulic Steering | Integrated | |
| Dynamic Power Steering | Integrated | |
| Trim Method | Power Trim & Tilt + i-Trim | |
| Trim Range | -6° to 15° | |
| Tilt Range | 81° | |
| Shaft Length - in | 20 | <input type="checkbox"/> |
| | 25 | <input type="checkbox"/> |
| | 30 | <input type="checkbox"/> |
| Lubrication | Multi-Point Targeted Oiling | |
| Oil Tank Capacity - L | On-Engine 7.5 | |
| Recommended Oil | Evinrude XD-100 | |
| Recommended Fuel | 87 Octane | |
| Counter Rotation | Available 25 and 30 inch | |
| Warranty | 5-Year Engine** / 5-Year Corrosion | |
| Emissions Compliance | EPA 2013 / CARB 3 STAR / European Union | |
| Integrated Features | Clean Dual Axis Rigging, i-Trim, auto-winterization, no break-in period | |
| Accessories | Evinrude E-Link, ICON 7.0 touch screen, cover, steering support brace, foot throttle, flush kit | |



⁽¹⁾ Price is valid with black or white panels, for other colors an up-charge is applied
^(*) Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V.
 Net dedicated battery charging power output is 50 Amp.

^(**) BRP 5 YEAR (STANDARD 3 + 2) This Extended Limited Warranty Program adds 24 months of BRP Limited Warranty coverage beyond the standard 36 month BRP Warranty applicable to Evinrude outboard engines under special conditions (see the Evinrude 2017 catalog for more details). Offered only through BRP European Distribution SA and its authorized BRP dealers for Evinrude® outboard engines that are sold to residents of the European Union for recreational use only.

EVINRUDE®

