

EVINRUDE® E-TEC® ENGINE SPECIFICATIONS

E 60

Engine Model	E60DSL <input type="checkbox"/> E60DPGL <input type="checkbox"/> E60DGTL <input type="checkbox"/>
Colour	White <input type="checkbox"/> Graphite <input type="checkbox"/>
Engine Type	Inline 2-Cylinder E-TEC
Bore x Stroke - mm	91 x 66
Displacement - cc	863
Gear Ratio	2.9:1
Full Throttle RPM Range	5500-6000 RPM
Weight - kg	109 <input type="checkbox"/> 113 <input type="checkbox"/>
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	81 Amps Total / 25 Net Dedicated
Steering	Remote <input type="checkbox"/> Tiller <input type="checkbox"/>
Trim Method	Power Trim and Tilt
Trim Range	-4° to 16°
Tilt Range	65°
Shaft Length - in	20
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L	1.9
Recommended Oil	Evinrude XD-100
Recommended Fuel	87 Octane
Warranty	5-Year Extended Limited Warranty**
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union
Integrated Features	Auto-winterization, no break-in period
Accessories	Tiller, ICON Pro gauges, flush kit, cover



* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

**BRP 5 YEAR (STANDARD 3 + 2) This Extended Limited Warranty Program adds 24 months of BRP Limited Warranty coverage beyond the standard 36 month BRP Warranty applicable to Evinrude outboard engines under special conditions (see the Evinrude 2017 catalog for more details). Offered only through BRP European Distribution SA and its authorized BRP dealers for Evinrude® outboard engines that are sold to residents of the European Union for recreational use only.

EVINRUDE®

