

# 150 HP

|                                    |  |
|------------------------------------|--|
| <b>Engine Model</b>                | (a) C150PL<br>(b) C150PX<br>(c) C150PXC                            |
| <b>Engine Type</b>                 | V6 66° E-TEC D.I.  |
| <b>Bore x Stroke - in (mm)</b>     | 3.386 x 3.100 (86 x 78.7)  |
| <b>Displacement - cu in (cc) L</b> | 167 (2744) 2.7L  |
| <b>Gear Ratio</b>                  | 2.17:1   |
| <b>Full Throttle RPM Range</b>     | 5000-6000 RPM  |
| <b>Weight - lbs (kg)</b>           | (a) 496 (225)<br>(b) 507 (230)<br>(c) 512 (232)                    |
| <b>Starting</b>                    | Electric   |
| <b>Controls</b>                    | Integrated Digital Shift & Throttle                                |
| <b>Fuel Induction</b>              | E-TEC Direct Injection with stratified low RPM combustion mode     |
| <b>Alternator Output*</b>          | 133 Amps Total / 50 net Dedicated / 14 amps @ idle                 |
| <b>Steering</b>                    | Remote   |
| <b>Trim Method</b>                 | Power Trim & Tilt  |
| <b>Trim Range</b>                  | -6° to 15°   |
| <b>Tilt Range</b>                  | 75°  |
| <b>Shaft Length - in (mm)</b>      | (a) 20 (508)<br>(b)(c) 25 (635)                                    |
| <b>Lubrication</b>                 | Multi-Point Targeted Oiling  |
| <b>Oil Tank Capacity - gal (L)</b> | On-Engine 3 (11.4) /<br>Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85) |
| <b>Recommended Oil</b>             | Evinrude/ Johnson XD-100 Oil                                       |
| <b>Recommended Fuel</b>            | 87 Octane  |
| <b>Counter Rotation</b>            | C150PXC  |
| <b>Warranty</b>                    | 5-Year Engine** / 5-Year Corrosion                                 |
| <b>Emissions Compliance</b>        | EPA 2013 / CARB 3 STAR / European Union                            |
| <b>Mounting Centers - in (mm)</b>  | Minimum 26 (660)   |
| <b>Color</b>                       | Slate Gray with over 400 Color Panel Options                       |
| <b>Steering Angle</b>              | +/- 30°  |
| <b>Integrated Features</b>         | i-Trim   |



\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V.  
Net dedicated battery charging power output is 50 Amp.

\*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.