

EVINRUDE® E-TEC® ENGINE SPECIFICATIONS

E 90

| | |
|-------------------------|---|
| Engine Model | E90DSL <input type="checkbox"/> E90DPGL <input type="checkbox"/> E90DPX <input type="checkbox"/> E90DGX <input type="checkbox"/> |
| Colour | White <input type="checkbox"/> Graphite <input type="checkbox"/> |
| Engine Type | Inline 3-Cylinder E-TEC |
| Bore x Stroke - mm | 91 x 66 |
| Displacement - cc | 1295 |
| Gear Ratio | 2.00:1 <input type="checkbox"/> 2.25:1 <input type="checkbox"/> |
| Full Throttle RPM Range | 5000-5500 RPM |
| Weight - kg | 145 <input type="checkbox"/> 152 <input type="checkbox"/> |
| Starting | Electric |
| Controls | Mechanical |
| Fuel Induction | E-TEC Direct Injection with stratified low RPM combustion mode |
| Alternator Output* | 81 Amps Total / 25 Net Dedicated |
| Steering | Remote |
| Trim Method | Power Trim and Tilt |
| Trim Range | -4° to 17° |
| Tilt Range | 75° |
| Shaft Length - in | 20 <input type="checkbox"/> 25 <input type="checkbox"/> |
| Lubrication | Multi-Point Targeted Oiling |
| Oil Tank Capacity - L | 2.3 |
| Recommended Oil | Evinrude XD-100 |
| Recommended Fuel | 87 Octane |
| Warranty | 5-Year Extended Limited Warranty** |
| Emissions Compliance | EPA 2013 / CARB 3 STAR / European Union |
| Integrated Features | Auto-winterization, no break-in period |
| Accessories | Tiller, ICON Pro gauges, flush kit, cover |



* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V.
Net dedicated battery charging power output is 25 Amp.

**BRP 5 YEAR (STANDARD 3 + 2) This Extended Limited Warranty Program adds 24 months of BRP Limited Warranty coverage beyond the standard 36 month BRP Warranty applicable to Evinrude outboard engines under special conditions (see the Evinrude 2017 catalog for more details). Offered only through BRP European Distribution SA and its authorized BRP dealers for Evinrude® outboard engines that are sold to residents of the European Union for recreational use only.

EVINRUDE®

